

When Failure is Not an Option!



HHC-SW

Hand-Held Controller

The newly developed WTI HHC-SW Hand-Held Controller is designed for field control and set-up of the C-Max Ultra Dome and the Sidewinder Pan/Tilt/Zoom cameras. Communication with the camera is implemented over the standard RS-485 data link, requiring no additional control wiring. Front panel control buttons allow quick, easy camera adjustment and set-up of every camera function during installation. This time saving tool enables every camera function to be remotely adjusted and fine tuned for optimum performance! Low power operation and an auto shutoff timer maximize battery life.

Features include:

- Compatible with WTI's C-Max Ultra Dome and Sidewinder P/T/Z cameras.
- No additional control wiring required to adjust all camera functions.
- Adjust camera operating parameters such as custom tours, alarm settings and all pre-set functions using only front panel high durability pushbuttons.
- High contrast display works in any lighting situation.
- Rugged weather resistant and shock resistant housing.
- Field upgradeable firmware for future enhancements.



2064 Eastman Avenue, Suite 113 ● Ventura, CA 93003-7787
toll free 866/gotowti (468.6984) ● fax 805/339.0932

Product Information - HHC-SW: Hand-Held Controller

WTI ~ HHC-SW: Hand-Held Controller

Electrical

Power	4 AA Alkaline Batteries
Battery Life Active	100 Hours (18mA operational current)
Battery Life Standby	3 Years (100uA standby current)
Auto Shutdown Timeout	Approximately 5 minutes from last button push

Environmental

Temperature	32° to 158° F (0° to 70° C)
Humidity	20% to 90% relative humidity (non-condensing)

Mechanical

Weight	15.2 oz. (430 grams) including batteries
Dimensions	8.5"L x 4.0"W x 2.25"H (216mmL x 102mmW x 57mmH)

Cable	6 foot (67cm) included with unit
-------	----------------------------------

Communications/Physical Layer

Interface	RS-232 and RS-422/485
Format	Pelco "D" Code and proprietary
Data Rate	2400, 4800, 9600, 19200 Baud

Basic Camera Functions

- Pan Right/Left
- Tilt Up/Down
- Zoom In/Out
- Focus In/Out
- Set Preset
- Set Tour

Advanced Camera Functions

(see manual)



WTI • 888/gotowti (468.6984) toll free • 805/339.9696 office • 805/339.0932 fax

Contact a WTI applications engineer to configure a system to perfectly suit your needs.

Due to Wireless Technology, Inc.'s continuing efforts to engineer the best product, that is most responsive to our customer's needs, the above specifications are subject to change.