

Product Information - VSMJP24D - C-MAX Ultra-Video Decoder

WTI ~ C-MAX Ultra-Video Decoder

www.gotowti.com



Features Include:

- Decodes MPEG 2/4, MJPEG video.
- Supplies high quality analog video and 2-way audio.
- Embedded Linux operation system
- Supports dynamic IP, PPPoE, DHCP.
- Dynamic OSD
- Data encryption/Watchdog security.



Video Input	1-ch Ethernet (RJ-45 10/100 Base-T)
Video Output	1-ch Analog BNC/S-Video (CVBS, NTCS or PAL)
Audio Input	1-ch Stereo Phone Jack Voice ADPCM 32Kbps@8KHz
Audio Output	1-ch Stereo Phone Jack Voice ADPCM 32Kbps@8KHz
Video Decoding	MPEG-2/4, MJPEG (involuntary)
Audio Decoding	ADPCM 32Kbps@8KHz
MAX Frame Rate	30 FPS @ 704x480 NTSC 25 FPS @ 704x576 PAL
Serial Interface	RS-422 (4-Pin terminal block), RS-485 (2-Pin terminal block)
Sensor/Alarm I/O	4-ch Terminal block
Operating System	Embedded Linux
Network Protocols	IPv4, TCP/IP, HTTP, SMTP, DHCP, PPPoE, ICMP, ARP, RARP, DNS, DDNS
Management	Web browser (Internet Explorer)
Security	Password, IP filtering, data encryption
Backup	USB 2.0
Indicator	Power LED, Network LED, Decode LED
Operating Temp.	0 *C ~ 50 *C Ambient
Size	4.7 x 1.2 x 3.9 in. (120 x 30 x 98.2mm)
Weight	12 oz. (343 g)

WTI • 888/gotowti (468.6984) toll free • 805/339.9696 office • 805/339.0932 fax

Contact a WTI applications engineer to configure a system to perfectly suit your needs.

Due to Wireless Technology, Inc.'s continuing efforts to engineer the best product, that is most responsive to our customer's needs, the above specifications are subject to change.