

Product Information - VSMJP24E - C-MAX Video Server/Encoder

WTI ~ C-MAX Video Server/Encoder

www.gotowti.com



Features Include:

- Multi-codec (MPEG 2/4, MJPEG).
- Stable operation based on embedded Linux.
- Watchdog.
- Interface with hybrid DRV for total management.
- Supports dynamic IP, PPPoE, DHCP.
- Different resolution/speed settings for display and recording.
- Display and record using USB 2.0 support.
- P/T/Z control, fully integrated.
- Built-in web server.
- Multicast and Internet streaming.
- Applied various networks.
- Built-in relay server program.

Operating System	Embedded Linux
Video In	1-ch BNC
Video Out	1-ch BNC
Audio In	1-ch
Audio Out	1-ch
Flash Memory	32 MB
Main Memory	32 MB
Power	DC 5V 2.4A Output
Compression Type	MPEG 2/4, MJPEG
Compression Level	4 level (superfine/fine/normal/low)
MAX Frame Rate	30 FPS @ 704x480 NTSC / 25 FPS @ 704x576 PAL
Resolution	704x480, 704x240, 352x240 NTSC / 704x576, 704x288, 352x288 PAL
LAN Port	Ethernet (10/100 base-T)
Interface	RJ45, RS-232, RS-485
Security	Password, IP filtering, data encryption
Backup	USB 2.0 / network
Sensor In	1 input
Relay Out	1 output
Indicator	Power LED, network status LED, relay & recording LED
Size	4.7 x 1.2 x 3.9 in. (120 x 30 x 98.2 mm)

WTI[®]
www.gotowti.com
An ISO 9001:2000 Certified Company

WTI • 888/gotowti (468.6984) toll free • 805/339.9696 office • 805/339.0932 fax

Contact a WTI applications engineer to configure a system to perfectly suit your needs.

Due to Wireless Technology, Inc.'s continuing efforts to engineer the best product, that is most responsive to our customer's needs, the above specifications are subject to change.