When Failure is Not an Option!

HHC-7000

Hand-Held Controller

Compatible with:

C-MAX Ultra/UltraLite Series Cameras

Ambervision

Features include:

- Compatible with WTI's C-MAX Ultra/UltraLite Series and Ambervision cameras.
- No additional control wiring required to adjust all camera functions.
- Adjust camera zoom setting using only front panel high durability pushbuttons.
- Auto shutoff timer feature to preserve maximum battery life.
- Rugged metal BNC connectors for extra reliability.

WTI®

www.gotowti.com

An ISO 9001 Certified Company

2064 Eastman Avenue, Suite 113 ● Ventura, CA 93003-7787

toll free 866/gotowti (468.6984) ● fax 805/339.0932

Product Information - HHC-7000: Hand-Held Controller

WTI ~ HHC-7000: Hand-Held Controller

Electrical	
Power	4 AA Alkaline Batteries
Battery Life: Active	100 Hours (18mA operational current)
Battery Life: Standby	3 Years (100uA standby current)
Auto Shutdown Timeout	Approximately 15 minutes from last button push or cable removal
Communications/Physical Layer	
Format	RS-232 modulated FSK on RF carriers
Data Rate	4800 Baud
Maximum Coax Length	500 feet RG-59/U or 600 feet RG-6/U
Camera Functions	
Controller Pushbuttons	Optical Zoom – Wide/Telephoto
Controller with PC and Camera Control Software	All camera functions
Environmental	
Temperature	32° to 158° F (0° to 70° C)
Humidity	20% to 90% relative humidity (non-condensing)
Mechanical	
Weight	10.5 oz. (300 grams) including batteries
Dimensions	7.875"L x 3.5"W x 1.5"H (200mmL x 89mmW x 38mmH)

Compatible with WTI's C-MAX Ultra/UltraLite and Ambervision cameras. Please check those individual spec sheets for more detailed information.

MADE IN THE USA

Contact a WTI applications engineer to configure a system to perfectly suit your needs.

Due to Wireless Technology, Inc.'s continuing efforts to engineer the best product, that is most responsive to our customer's needs, the above specifications are subject to change.